ECHNICAL INFORMATION




For Models > 2412N

Description ► 305MM/355MM PORTABLE CUT-OFF

Conception and main applications

The #2412N is the remodeled type of #2412 and the design is renewed, which has been developed while aiming at low cost, easy-to-use and safety to satisfy the request from the sales field.

Also, the #2414 is the sister version of it, wherein the grindstone with diameter 355 mm is installed compared with the #2412N with 305 mm to cope with the users' demand for much larger diameter grindstone.



Specifications

Motor			Series commutator motor
Voltage			Single phase 100V
Cycle			50/60Hz
Consumed power			1450W
No Load Speed			3800r.p.m
Wheel Dia. Ø #2412N		#2412N	305mm
		#2414	355mm
Max. cutting at 90 degrees		es	ø 100mm W 190 mm
capacities	at 45 degrees		ø 100mm W 100 mm
Net Weight #2412N #2414		#2412N	15.7kg
		#2414	17kg
Cord lenght			5m

► Standard equipment

#2412N Box wrench 17 --- 1pc.

Cut-off-wheel 305 --- 1pc.

#2414 Box wrench 17 --- 1pc.

Cut-off-wheel 355 --- 1pc.

Optional accesories

Cut-off-wheel 305(5-pc.--- one set)

Cut-off-wheel 355 (5-pc.--- one set)